

LSM-80/LSM-80D Tube Roller

LSM-80/LSM-80D Tube roller is widely used in mixing blood sample, sticky substance and Solid-liquid suspension, etc. It provides two operation modes – rolling and swinging to improve mixing efficiency and safety. It is applied in preventing blood clotting, immunoprecipitation, and other similar using.



10~80 rpm
Speed Range



360 angle
Two mode
360 Angle



LED Display



Most Test Tube
Different Kinds
Tubes



[Product Features]

1. Compact and firm designed, simple operation, LED display time and speed.
2. Two types choosable – rolling type and rolling & swinging type. Continuous working mode, safe and stable.
3. With stable performance motor, operation speed adjustable, max. speed to 80rpm. Low noise, long using life.
4. Compatible with different size of tubes. Large range of application.

[Technical Parameters]

Model	LSM-80	LSM-80D
Speed Range	10rpm ~80rpm	10rpm ~80rpm
Operation Mode	rolling and fluctuation	rolling
Amplitude	25mm	/
Roller Quantity	6	6
Roller Length	280mm	280mm
Max. Load	4kgs	4kgs
Time Range	1min ~99h59min or continuous	1min ~99h59min or continuous
Voltage	AC 100 ~230V, 50/60Hz	AC 100 ~230V, 50/60Hz
Power	25W	25W
Fuse	250V, 1A, Φ 5x20	250V, 1A, Φ 5x20
Dimension (WxDxH)	450 x 260 x 120mm	450 x 260 x 120mm
Net Weight	3.7kgs	3.7kgs